PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H04N 7/08, 7/10, 11/00, H04H 1/02, 7/00

(11) International Publication Number:

WO 97/29591

A1 |

(43) International Publication Date:

14 August 1997 (14.08.97)

(21) International Application Number:

PCT/US97/01849

(22) International Filing Date:

7 February 1997 (07.02.97)

(81) Designated States: AU, CA, IL, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(30) Priority Data:

08/597,432

8 February 1996 (08.02.96)

US

Published

With international search report.


(71)(72) Applicant and Inventor: WOLZIEN, Thomas, R [US/US]; 41 River Road, Grandview, NY 10960 (US).

(74) Agents: BERGER, Michael, J. et al.; Amster, Rothstein & Ebenstein, 90 Park Avenue, New York, NY 10016 (US).

(54) Title: MEDIA ONLINE SERVICES ACCESS SYSTEM AND METHOD

(57) Abstract

A system is disclosed for providing direct automated access to an online information services provider (34a, 34n) through an address embedded in a video or audio programm, commercial message, or news story. The system operates with video or audio programs (15) which are received through broadcast, cable or pre-recorded media, and which are encoded in either analog or digital formats. The address of an online information provider is encoded in a vertical blanking interval or other nondisplayed portion of an electronic signal which represents the video or audio program so as not to interfere with the programs as displayed or transduced on a television or audio sound system (22, 40). The online information provider address is detected and decoded from the electronic signal and used in establishing a direct digital communication link to the online information provider (34a, 34n).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| AM | Armenia | GB | United Kingdom | MW | Malawi |
|-----|--------------------------|----|------------------------------|-----|--------------------------|
| ΑT | Austria | GE | Georgia | MX | Mexico |
| AU | Australia | GN | Guinea | NE | Niger |
| BB | Barbados | GR | Greece | NL | Netherlands |
| BE | Belgium | HU | Hungary | NO | Norway |
| BF | Burkina Faso | Œ | Ireland | NZ | New Zealand |
| BG | Bulgaria | IT | Italy | PL. | Poland |
| BJ | Benin | JP | Japan | PT | Portugal |
| BR | Brazil | KE | Kenya | RO | Romania |
| BY | Belarus | KG | Kyrgystan | RU | Russian Federation |
| CA | Canada | KP | Democratic People's Republic | SD | Sudan |
| CF. | Central African Republic | | of Korea | SE | Sweden |
| CG | Congo | KR | Republic of Korea | SG | Singapore |
| CH | Switzerland | KZ | Kazakhstan | SI | Slovenia |
| CI | Côte d'Ivoire | u | Liechtenstein | SK | Slovakia |
| CM | Cameroon | LK | Sri Lanka | SN | Senegal |
| CN | China | LR | Liberia | SZ | Swaziland |
| CS | Czechoslovakia | LT | Lithuania | TD | Chad |
| CZ | Czech Republic | LU | Luxembourg | TG | Togo |
| DE | Germany | LV | Latvia | TJ | Tajikistan |
| DK | Denmark | MC | Monaco | TT | Trinidad and Tobago |
| EE | Estonia | MD | Republic of Moldova | UA | Ukraine |
| ES | Spain | MG | Madagascar | UG | Uganda |
| FI | Finland | ML | Mali | US | United States of America |
| FR | France | MN | Mongolia | UZ | Uzbekistan |
| GA | Gabon | MR | Mauritania | VN | Viet Nam |

MEDIA ONLINE SERVICES ACCESS SYSTEM AND METHOD

The present invention relates to an electronic information access system and more specifically to a media online services access system which provides 5 direct, automated access to online information an provider through an address embedded in an electronic signal which carries a program segment (e.g., through television, radio, or a pre-recorded video or audio medium).

10 BACKGROUND OF THE INVENTION

30

Heretofore, media receiving and display systems such as television and radio receivers have been linked interactive information providers in only limited ways. Some systems exist which permit the 15 exchange of digital information with the viewer of a television program over or in combination with television signal, but such systems have provided access to a single information source available from, for example, the broadcast or cable television operator. such systems, the selection of information services has been entirely within the control of the broadcast or cable television operator. At the same time, some television and radio broadcasters have begun announcing an Internet address for viewer inquiries during the 25 course of program transmission. Access to this Internet address requires the user to utilize his or computer. No system yet exists which provides automated and direct user access to online information providers through an address embedded in a video or audio program signal.

The recent explosion in the usage of online information services through digital networks such as the Internet, Prodigy (R), America Online (R) Compuserve (R), for example, indicate that the demand for access to readily available up-to-date or detailed information is increasing. The viewer of a video program, whether the program is received through

broadcast, or cable means or from a pre-recorded medium, may often seek to discover more information which relates to a topic presented in the video program. Since television programs and recordings are of finite length, they do not contain all the related information which a consumer may wish, and the information contained therein may not be timely. Therefore, it would be desirable for there to be a system which automatically and directly provides access to an online information provider through an address which can be extracted from an audio or video program such as a television program, commercial or news story. With such system, several benefits would be obtained. For example, adults and children viewing an educational or historical video program could easily locate additional materials provided in text or still picture by the producers of the video program by accessing more information from the producers digitally through the online Consumers seeking more information about a specific advertised product could easily find such information by 20 accessing the online address of an information provider designated by the advertiser. News program viewers seeking specific information from news stories or more information could detailed easily access 25 information through an online information provider designated by the producers of such program.

The online services access system could be used to provide still other benefits to consumers, business owners, and the government. For example, an automobile manufacturer could make information available directly to a consumer through an online address embedded in a video presentation so the consumer could reach its online site quickly to ask for more information, to request a test drive, or to purchase parts. Through such system, a grocery store could advertise and receive orders through its online site from customers for home delivery, or for other shopping needs. A catalog

retailer could use such system to provide rapid access to consumers, after airing a commercial, to its catalog in online form and to enable orders to be placed readily through its online site. A record company could use such system to enable customers to order a recording while listening to a song or viewing a music video. Government agencies, e.g., the Internal Revenue Service, military recruiters, or health agencies, for example, could use such system to provide consumers with readily available information following the airing of public 10 service announcements regarding regulations, programs, or public health concerns, e.g., cancer, AIDS, and heart disease. Educators and students could use such system to obtain more detailed or up-to-the-minute information from online bulletin boards and databases regarding topics presented in a video program, even though the program was recorded some time in the past.

Systems exist at present in which digitally encoded information is transmitted and received through a modified video signal of a conventional television transmission. For example, a system is described in U.S. Patent No. 4,894,789 wherein a digital information signal is transmitted during the vertical blanking interval of an analog broadcast television signal and decoded and displayed on the television screen in addition to the analog broadcast video signal.

U.S. Patent No. 5,128,752 describes a system in which a retailer broadcasts information for reception upon a conventional television set regarding products available through a central location. The system includes decoder for displaying the product information on the television screen, and also a token generator for producing tokens, at the user's option, to be redeemed when a product is purchased. The broadcast information includes data related to token redemption and value considerations available upon purchase of the product.

-4-

U.S. Patent No. 5,285,278 describes a system in which coupon-related digital information is received from a transmitted television signal through a decoder. The decoder records the coupon-related data for later readout and redemption when a product is purchased.

U.S. Patent No. 4,905,094 ("the '094 Patent") describes an interactive cable television system in which a subscriber tunes to a channel and requests connection to a remote location by either dialing a 10 predetermined telephone number or accessing a cable television channel. When the system identifies the subscriber the television set displays the frame of video (and possibly accompanying audio information) describing products or services which may be viewed and 15 purchased. The '094 Patent does not describe extraction of encoded address information from the television signal, or a system enabling a television program viewer to access online information providers by establishing connection automatically through 20 extracted address.

Thus, systems exist which are capable of providing interactive user access through a broadcast or cable television signal. However, such systems are limited in the access they provide to information sources directly available through the unitary cable or broadcast provider. By contrast, the present invention facilitates direct automated user access to an unlimited number of online information providers through provider addresses which are embedded in the electronic signal which carries an video or audio program.

Accordingly, it is an object of the invention to provide a system for extracting an address of an online information provider from an electronic signal which carries an video or audio program.

It is a further object of the invention to provide a system which indicates to the program user (i.e., viewer or listener), after extracting an online

information provider address, that more information is available.

Still another object of the invention is to provide an automated system which, upon receipt of a 5 single user command, directly and automatically establishes а digital connection with an information provider through an address extracted from an electronic signal which carries a video or audio program.

10 Another object of the invention is to provide a system which converts information signals received from an online information provider to a form capable of being displayed on a conventional reproducing system such as a television set.

15 These and other objects are provided by the media online services access system of the present invention.

SUMMARY OF THE INVENTION

The media online services access system of the present invention provides a system and process which links video and audio program content with online information signal content. The system heretofore unattained direct automated user access from a media program such as a received or pre-recorded 25 television OI radio (audio) signal to an information provider through a link provided in the media program. The access system receives an electronic signal representing a video or audio program or a combined audio/video program from an available medium (e.g., broadcast and cable television and radio, or a pre-recorded medium such as a tape or disc). in the electronic signal, for example, in the vertical blanking interval, or otherwise encoded electronic signal in such manner as not to interfere with the displayed image, is an information signal representing electronic an address of information provider. The online information provider

-6-

can be any one of millions of interactive information providers which can be accessed through exchange of digital information signals, for example, a publisher who is available through the Internet for interactive transactions. As the media program is received for reproduction on a video display or audio sound system, the access system extracts the embedded electronic address for use in directly accessing the online information provider at the selection of the user.

Preferably, the address is stored at the time 10 of extraction. for use in accessing the online information provider at the selection of the user. duration in which an extracted signal address is stored may be relatively short, as in the case where the address is transmitted and refreshed continuously or at 15 very short intervals, e.g., once per each frame of a video signal, or it may be longer, as when an address is transmitted only at selected intervals of a program.

successfully extracting an electronic address, the access system provides a indicator signal 20 to the user that more information is available. indicator signal may take the form of a displayed on a video screen, or other indicators such as a light, a sound or a wireless tactile indicator, e.g., 25 vibrating wristband or clip-on unit. Alternatively, the video or audio program may contain a logo or message to be displayed for the user at points in the program which coincide with the presence of an embedded information provider address, which, in such case, would 30 eliminate the need for the access system to incorporate specific structure to provide indication to the user, in response to successful extraction of an online provider address.

After receiving the indicator signal, if the user desires more information, the user may request access to the online information provider through a command to the access system, e.g., through pushbutton,

-7-

user control keypad, voice command, mouse, touchpad, touchscreen, or other such input. Upon receiving such command, the access system automatically establishes a digital communication link with the online information provider through transmission of a signal containing the extracted address. Preferably, upon establishment of such communication link, the access system enables interactive communications with the online information provider.

10 In another embodiment of the invention, extracted address can be used without first being stored, as in cases where a connection already exists between the access system and a network. Where such connection exists, the access system provides indicator signal to the user upon successful extraction 15 of an online information provider address. this embodiment, the access system waits to receive a command initiate to access, and only receiving such command does the access system extract the next received address from the electronic signal and use it to establish a direct connection to the online information provider.

In a preferred embodiment, after accessing an online services provider, the access system receives information from the online information provider and processes it for reproduction on a video or audio reproducing system. For example, the information can be displayed on the television screen in place of the television broadcast signal, on a separate computer monitor or other display device, or together with the television broadcast signal in a picture-in-picture In this way, the user can fully explore all of format. related information available from the information provider. Preferably, the access system is provided with hardware to reformat the received information signal for display upon an otherwise incompatible system, for example, to convert a digitally

25

30

35

video encoded signal to an analog signal for reproduction on а conventional television set. Preferably, the access system is also provided with hardware for receiving and processing user commands for 5 transmission to the online information provider for providing user communication transactions with the provider.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block and schematic diagram 10 illustrating the online services access system accordance with the present invention.

FIG. 2 is a block and schematic diagram of an access controller used in the online access system of FIG. 1.

15 FIG. 3 is a block and schematic diagram of another embodiment of an access controller used with a computer in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

- An online services access system according to 20 the present invention is illustrated in Referring to FIG. 1, the online services access system includes access controller 10 which incorporates components necessary to provide online access and to access received online information signals. Access 25 controller 10 is constructed to receive an electronic signal 12 from a broadcast, cable or prerecorded medium program in conventional form from a video signal source Video signal source 14 can be selectively switchable to provide output from a channel selector 16 30 connected to a cable or broadcast video input 15 or from a video playback system 18 which may be, for example, a videocassette recorder or an analog or digital videodisc device. It will be appreciated that channel selector 16 may be provided in a unit separate from playback system 35 18, OI within access controller 10 itself. Alternatively, access controller 10 can be constructed
- to receive and decode program signals at radio frequency

as received from a broadcast or cable video source, or as downconverted to baseband, by for example, the front end receiving circuitry of a video cassette recorder or digital video disc device. It will also be appreciated that the function and results provided by access controller 10 are not dependent upon which of many available playback systems is connected thereto, whether such systems are analog or digital in format, or whether such playback systems operate upon videotape, audiotape, or disc media.

Access controller 10 is connected via a primary output signal line 36 to a conventional reproducing system 22 such as a television set, and is optionally connected through a second output signal line 38 to a high resolution reproducing system 40, 15 such computer monitor. In addition, access controller 10 is connected to a public or private network 30 through an information signal carrier 32, e.g., telephone line, coaxial cable, fiber optic link, cellular, 20 radiotelephone, or satellite link. Network 30, which may be any private or public local area network or wide area network such as an office network, company network, public Internet or circuit-switched network is used to route address and information signals between access controller 10 and a selected one of a plurality of online information providers 34a, 34b, 34c, . . . 34n. Access controller 10 receives from the information provider, through network 30, information signals having a video or audio program content and selectively provides, through appropriate conventional processing, a conventional program signal or a high resolution signal for reproduction upon reproducing system 22, or high resolution reproducing system 40, respectively.

The internal construction of access controller lo is described with reference to FIG. 2. Access controller lo is provided with an address extractor 42

PCT/US97/01849

receives electronic signal 12. the Address extractor 42 includes hardware and/or software detect, decode and store an address which has been embedded in a video or audio program signal. Among the 5 ways which exist to detect an address signal transmitted in conjunction with an analog video signal, extractor 42 may be constructed to detect a digital address which is transmitted during a vertical blanking interval or other portion of a conventional video signal such manner that displayed image quality is not 10 For example, the address signal can affected. transmitted during a portion of a video signal such as in the vertical interval, in sync or through changes in the luminance or chroma signals. Address extraction 42 is constructed to electronically store, e.g., via a register or memory device (not shown), the detected address for accessing the online use in services provider at the selection of the user. signal may be transmitted at very short intervals, e.g., 20 once for each frame of a video program such that storing and refreshing of the extracted address signal occurs at very short intervals. Alternatively, the address signal may be transmitted at longer intervals, discrete intervals in a program such that the duration 25 in which an extracted address signal is stored is much longer.

In such cases in which video or audio program is encoded digitally, address extractor 42 may be constructed in any of several existing ways to detect an address signal which is received in conjunction with a digitally encoded video or audio electronic signal 12. The details of the construction of address extractor 42 are well known in the art and need not be described in further detail.

Address extractor 42 has an output connection to an indicator signal generator 46. The indicator signal generator 46 signals the user that more

WO 97/29591

PCT/US97/01849

information relating to the program is available, such information being accessible through an electronic address when address extractor 42 has decoded such address from the electronic signal 12. Indicator signal 5 generator 46 causes, for example, a video image (e.g., picture within picture, logo, or icon) to be displayed with the video program signal on reproducing system 22 to signal the user that an address of an online provider has been stored and that additional 10 information is available. Instead, or in addition to such visual display, indicator signal generator 46 may signal the user by activating a light 24 or other visual indicator located on an exterior panel of access controller 10 OI of reproducing system 22. 15 Alternatively, indicator signal generator may cause a sound to be produced on a speaker 26 of reproducing system 22, or by a speaker 28 provided in access Here again, the design of indicator controller 10. signal generator 46 is well known in the art.

20 Access controller 10 is provided with a user input interface 56 for receiving a user command which automatically initiates establishment of digital communication link to an online information provider through an address detected from the electronic 25 signal 12 address by extractor 42 and permits interactive communication between the user online information provider. It will be appreciated that many conventional input interfaces are well suited use as user interface 56 because compatibility with conventional television and audio systems. Among such input interfaces infrared, radio and audio frequency interfaces which decode single key or multiple key sequence input from a wired or wireless remote user control. Preferably, user input interface 56 detects when a special purpose button on a remote user control has been pressed and provides a responsive signal which automatically causes the stored

address of the online provider to be retrieved transmitted. User input interface 56 can constructed to detect when a special sequence of keys has been pressed on a conventional user control (e.g., a 5 sequence such as "ENTER," "ENTER," "+VOLUME") and to enable interactive communication with the online information provider. Alternatively, user interface 56 can be implemented by any appropriate microcomputer type user interface, e.g., 10 touchpad, touchscreen, trackball, joystick, pushbutton, eraser head, or other such device. Preferably, user interface 56 is constructed to provide and receive transmission of digital information signals through modem 54 to the online information provider, thereby 15 enabling interactive user access with the online provider for conducting detailed information searches, conducting transactions, and sending or posting messages to the accessed provider.

Access controller 10 is provided with a modem 20 54 for transmitting and receiving digital information signals between access controller 10 and public switching network 30 through an information signal carrier line 32. Modem 54 demodulates information signals and outputs them to processor 58 25 which extracts a video and/or an audio signal Preferably, access controller 10 includes a converter 62 for adjusting or converting an incompatible signal for display upon conventional reproducing system 22, such as a television set, either in place of the 30 television signal, superimposed over the television signal, or in picture-in-picture format, as controlled by the user. Alternatively, processor 58 provides the video signal on line 38 to a high resolution reproducing system 40, such as a computer monitor. Indicator signal generator 46 may also incorporate a switch (not shown) which automatically switches off the primary output signal 36 whenever a signal appears at the output of

signal converter In this 62. manner, information signals received from online information providers will be automatically displayed on conventional reproducing system 22 in place of the ordinarily displayed video Processor 58 can also receive the input 5 signal 36. video or audio electronic program signal through a line 55 output from address extractor 42 (although direct connection of the electronic signal line 12 possible). In this manner, processor 58 may 10 constructed to operate upon the video or audio signal in conjunction with information signals received from an online information provider to generate a within picture" signal for display upon conventional reproducing system 22.

15 The operation of the system will An electronic signal 12, such as a signal described. from a video or audio program from channel selector 16 or playback system 18, e.g., prerecorded videotape, or an analog or digital video disc, containing an embedded signal representing the electronic address of an online information provider in the blanking interval or other non-displayed portion of the electronic signal 12 is received by address extractor 42. From the electronic signal 12, address extractor 42 detects, decodes and 25 stores a digital address of the online services provider, if any such address is embedded therein. an address is successfully decoded and stored, address extractor 42 activates, through signal line 44, indicator signal generator 46. Indicator signal generator 46 then produces an indicator signal overlays or encodes it onto a conventional signal 36 to be displayed or transduced by conventional reproducing system 22. Alternatively, indicator signal generator 46 produces a signal on line 50 activates а special purpose indicator, e.g., illuminating a light 24 or producing a sound on a speaker 28 of access controller 10.

-14-

Ιf the user wants to access the online information provider, the user gives such command to access controller 10 by, for example, pushing a special button on his or her remote control device. The remote 5 control device transmits a command signal to interface 56 which receives the command signal. interface 56 in turn, produces a signal which is applied to address extractor 42 to retrieve the stored address of the online information provider. Under appropriate 10 software or hardware control, the address is transmitted via modem 54 over network 30 to an online information provider, e.g., 34c.

Once access to the online information provider has established, access controller 10 15 automatically receive digital information signals through modem 54 from the online information provider. information signals are operated upon processor 58 for displaying conventional upon TV reproducing system 22 or high resolution reproducing 20 system 40, e.g., a computer monitor or other display device. Preferably, received signals which incapable of being directly displayed upon conventional reproducing system 22, e.g., a conventional television set, are converted by a signal converter 62 for display 25 thereon. Information signals received from an online information provider may be displayed as still or moving images in place of the ordinarily displayed video signal on the conventional reproducing system 22, or may be displayed as part of a "picture within picture" display in conjunction with the ordinarily displayed video signal on conventional reproducing system 22 or on the computer monitor 40 or other display device.

After access has been established. user commands received through interface user 56 transmitted as information signals through modem 54 to information provider, online thereby providing interactive user access with the online provider and

enabling searching for detailed information, conducting transactions, sending or posting messages to the accessed provider and any other actions that can ordinarily be conducted through an online connection.

5 Another embodiment of the invention is illustrated in FIG. 3. FIG. 3 shows an embodiment which operates in conjunction with an available computer 164. In this embodiment, access controller 110 does not require an internal processor or modem because such 10 functions are provided by a computer 164 In addition, computer 164 also provides a thereto. monitor and audio reproducing components which function as high resolution reproducing system 40. extractor 142, indicator signal generator 146, and user interface 156 of access controller 110 connected through an output interface 166 for providing decoded address output, indicator signals, commands, respectively, to computer 164. In other respects, access controller 110 is connected to receive 20 an electronic signal 12 and provide a conventional program signal 122 and a signal 150 to indicator 124 or indicator 128, in like manner as in the self-contained embodiment of access controller 10 described in the foregoing (FIG. 2). It will be appreciated that the computer supported embodiment of the invention (FIG. 3) provides the same function and operates in essentially the same manner as the self-contained embodiment (FIGS. 1-2) and need not be described in any further detail.

In still another embodiment of the invention,
with reference to FIGS. 1-3, a connection to network 30 is maintained continuously by access controller 10 through modem 54 or the modem provided in computer 164. This embodiment will be described with reference to the access controller 10 shown in FIG. 2, although the skilled person in the art will readily understand the structural modifications required for operation in accordance with the access controller shown in FIG. 3.

In this embodiment, address extractor 42 detects and decodes an online information provider address embedded in the video or audio program signal, but does not store the address.

5 As described in the foregoing embodiments of the invention, address extractor 42 provides a signal to indicator signal generator 46 when it successfully detects an online information provider address in the electronic signal. Address extractor 42 detects and 10 decodes the embedded address and passes it to modem 54. Modem 54, in turn, only uses the extracted address if it has first received a user command to initiate access to the online information provider. It will be appreciated that this embodiment of the invention can be used with a 15 video or an audio program signal wherein the online information provider address is frequently continuously transmitted. Modem 54 is provided with hardware and/or software to automatically establish, upon receiving a user command to initiate online access, a direct digital communication link with the online information provider associated with the next received online information provider address.

an example of the operation of non-address storing embodiment of the invention, a video 25 an audio program signal having frequently transmitted embedded signal containing an information provider address is received through line 12 by address extractor 42. Address extractor 42 detects and decodes the online information provider address, but does not store it before passing it to modem 54. Modem 30 54 does nothing with the online information provider address unless a user command to initiate access has first been received from user interface 56. user command has been received, modem 54 transmits a 35 signal over network 30 using the next received address to establish a digital communication link with the online information provider. The function and operation

of the non-address storing embodiment is otherwise the same as in the other described embodiments of the invention and need not be described in any further detail.

5 In yet another embodiment of the invention, automated direct user access to online information providers is achieved without incorporating an indicator signal generator 46, 146 (FIG. 3) into the access controller 10. In this embodiment, the video or audio program as produced incorporates a visual or auditory indicator, such as а logo or message, which automatically displayed or sounded by conventional reproducing system 22 and/or high resolution reproducing system 40 during portions of the program when an online 15 information provider address is present underlying electronic program signal. Through visual or auditory indicator, the user is made aware of the availability of the online information provider address. Therefore, in this embodiment of the invention, address extractor 42 may be constructed and used in a manner so as to detect and decode an embedded online information provider address only after receiving user command to initiate access to the online information provider. The skilled person in the art 25 will appreciate that this embodiment of the invention operates in other respects as in the other embodiments of the invention described in the foregoing and need not be described in further detail.

While the invention has been particularly described and illustrated with reference to preferred embodiments thereof, it will be understood by those skilled in the art that changes in the above description or illustration may be made with respect to form or detail without departing from the spirit and scope of the invention.

-18-

WHAT IS CLAIMED IS:

10

30

A method of providing to a user of online information services, at the time of viewing a video program represented by an electronic signal, direct digital communication access to an online information provider through a link provided in said video program, comprising:

electronically extracting an address associated with an online information provider from an information signal embedded in said electronic signal;

indicating to the user that an address has been extracted permitting communication with an online information provider; and

automatically using said extracted 15 address, in response to a user initiated command, to establish a direct digital communication link with the online information provider associated with said extracted address.

- 2. The method in accordance with Claim 1
 20 further comprising using said direct communication link
 to provide interactive exchange of information between
 said online information provider and the user.
- 3. The method in accordance with Claim 1 wherein said step of indicating includes producing a 25 visual indication to be displayed on the system wherein said program is displayed.
 - 4. The method in accordance with Claim 1 wherein said step of indicating includes producing an auditory indication to be sounded on a speaker where an audio portion of said program is reproduced.
 - 5. The method in accordance with Claim 1 wherein said step of indicating includes activating a sensory indicator on a system separate from that on which said program is reproduced.
- 35 6. The method in accordance with Claim 1 wherein said step of indicating further includes indicating that more information relating to the content

of said video program is available through said extracted address.

7. A method of providing online information services to a user of such online services, comprising5 the steps of:

providing an audio or video signal having an embedded information signal representing the address of an online information provider;

extracting and storing the address of said 10 online information provider from said audio or video signal;

automatically using said stored address, in response to a user initiated command, to transmit a signal to connect said user with the online information provider associated with said stored address; and

receiving online information signals from said online information provider.

8. A method of providing to a user of online information services, at the time of viewing a video program represented by an electronic signal, direct digital communication access to an online information provider through a link provided in said video program, comprising:

indicating to the user that an address is available for extraction from said electronic signal which permits communication with an online information provider;

automatically electronically extracting, in response to a user initiated command, an address associated with an online information provider from an information signal embedded in said electronic signal, and using said extracted address to establish a direct digital communication link with the online information provider associated with said extracted address.

9. A media online services access system for providing to a user of online information services, while viewing or listening to a video or audio program

15

WO 97/29591 PCT/US97/01849

represented by an electronic signal, a direct digital communication link with an online information provider through a link provided in said electronic signal, comprising:

-20-

electronic detecting means for extracting an address associated with an online information provider from an information signal embedded in said electronic signal;

means for indicating to the user that an 10 address has been extracted which permits communication with an online information provider; and

means responsive to a user initiated command for automatically establishing a direct digital communication link with the online information provider associated with said extracted address.

10. The media online services access system in accordance with Claim 9 wherein said program is a video program, further comprising:

means for receiving an information signal 20 from said online information provider; and

means for displaying an image signal detected from said received information signal.

- 11. The media online services access system in accordance with Claim 9 wherein said indicating means comprises a visual indicator displayed on a system on which said program is displayed.
 - 12. The media online services access system in accordance with Claim 9 wherein said program is an audio program.
- 13. The media online services access system in accordance with Claim 9 further comprising a user control device coupled to said system to permit said user to interactively communicate with said online information provider.
- 35 l4. The media online services access system in accordance with Claim 9 wherein said means further includes means for indicating that more information

20

25

WO 97/29591 PCT/US97/01849

relating to the content of said video program is available through said extracted address.

-21-

- 15. A media online services access system for providing to a user of online information services, while viewing or listening to a video or audio program represented by an electronic signal, a direct digital communication link with an online information provider through a link provided in said electronic signal, comprising:
- means for extracting and storing an address associated with an online information provider from an information signal embedded in said electronic signal;
- means for indicating to the user that an l5 address has been extracted which permits communication with an online information provider; and

means responsive to a user initiated command for automatically establishing a direct digital communication link with the online information provider associated with said stored address.

- 16. The media online services access system in accordance with Claim 15 wherein said means further includes means for indicating that more information relating to the content of said video program is available through said extracted address.
- 17. A media online services access system for providing to a user of online information services, while viewing or listening to a video or audio program represented by an electronic signal, a direct digital communication link with an online information provider through a link provided in said electronic signal, comprising:

means for indicating to the user that an address is available for extraction from said electronic signal which permits communication with an online information provider; and

means responsive to a user initiated

-22-

command for extracting an address associated with an online information provider from an information signal embedded in said electronic signal, and for automatically establishing a direct digital communication link with the online information provider associated with said extracted address.




FIG. 1

SUBSTITUTE SHEET (RULE 26)





FIG. 2



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/01849

| A CLA | SCIEICATION OF SUBJECT MARRIED | | | | | | |
|---|--|---|---------------------------------------|--|--|--|--|
| A. CLASSIFICATION OF SUBJECT MATTER | | | | | | | |
| IPC(6) : Please See Extra Sheet. US CL : Please See Extra Sheet. | | | | | | | |
| | o International Patent Classification (IPC) or to both | national classification and IPC | | | | | |
| B. FIELDS SEARCHED | | | | | | | |
| Minimum documentation searched (classification system followed by classification symbols) | | | | | | | |
| i | | o by classification symbols, | | | | | |
| 0.3. : | Please See Extra Sheet. | | | | | | |
| Documentat | ion searched other than minimum documentation to the | e extent that such documents are included | in the fields searched | | | | |
| | | | | | | | |
| | | | | | | | |
| Electronic d | lata base consulted during the international search (n | ame of data base and, where practicable. | search terms used) | | | | |
| | 3 (| 0. <u></u> 2, p | | | | | |
| | | | | | | | |
| | | | | | | | |
| C. DOC | UMENTS CONSIDERED TO BE RELEVANT | | | | | | |
| Category* | Citation of document, with indication, where a | ppropriate, of the relevant passages | Relevant to claim No. | | | | |
| A | US 5,262,860 A (FITZPATRICK | et all 16 November 1993 | 1-17 | | | | |
| | see whole document. | 2. 2., 10 110 1011001 1000, | | | | | |
| | | | | | | | |
| | | | | | | | |
| A | US 5,438,355 A (PALMER) 01 | August 1995 see whole | 1-17 | | | | |
| | document. | August 1550, See Whele | • • | | | | |
| | | | | | | | |
| | | | | | | | |
| A,E | US 5,604,542 A (DEDRICK) 18 | Enhauser 1997 and whole | 1-17 | | | | |
| ~,~ | document. | rebluary 1997, see whole | 1-17 | | | | |
| | document. | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| ľ | | | | | | | |
| | | | | | | | |
| , | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Furth | er documents are listed in the continuation of Box (| See patent family annex. | | | | | |
| | cial categories of cited documents: | *T* later document published after the inter date and not in conflict with the applica | mational filing date or priority | | | | |
| "A" doc to b | nument defining the general state of the art which is not considered be part of particular relevance | principle or theory underlying the inve | | | | | |
| | ier document published on or after the international filing date | "X" document of particular relevance; the | | | | | |
| "L" doc | ument which may throw doubts on priority claim(s) or which is | considered novel or cannot be consider when the document is taken alone | on en magino en magerias est ò | | | | |
| abo care | d to establish the publication date of another citation or other cial reason (as specified) | "Y" document of particular relevance; the | | | | | |
| O. qoo | nument referring to an oral disclosure, use, exhibition or other | considered to involve an inventive combined with one or more other such | documents, such combination | | | | |
| 'P' doo | ument published prior to the international filing date but later than | being obvious to a person skilled in the '&' document member of the same patent i | | | | | |
| the | priority date claimed | | | | | | |
| Date of the actual completion of the international search Date of mailing of the international search report | | | | | | | |
| 23 MARCH 1997 | | | | | | | |
| Name and mailing address of the ISA/US Authorized officer / | | | | | | | |
| Commission Box PCT | er of Patents and Trademarks | B. F. Budw/ | | | | | |
| Washington, D.C. 20231 JOHN W. MILLER | | | | | | | |
| Pacaimile No | o. (703) 305-3230 | Telephone No. (705) 305-4795 | | | | | |

INTERNATIONAL SEARCH REPORT

International application No. PCT/US97/01849

| A. CLASSIFICATION | OF SUBJECT | MATTER |
|-------------------|-------------------|---------------|
| IPC (6): | | |

H04N 7/08, 7/10, 11/00; H04H 1/02, 7/00

A. CLASSIFICATION OF SUBJECT MATTER: US CL :

348/6, 10, 465, 476; 455/6.2, 6.3

B. FIELDS SEARCHED Minimum documentation searched Classification System: U.S.

348/6, 7, 9, 10, 12, 13, 461, 465, 469, 473, 476, 477, 478, 479; 455/3.1, 4.1, 4.2, 5.1, 6.1, 6.2, 6.3; HO4N 7/00, 7/08, 7/087, 7/10, 11/00